

Fully threaded rod acid resistant A4-70 (316)



Fully threaded rod(HGS)

Stock programme:

M4, M5, M6, M8, M10, M12, M14, M16, M18, M20, M22 and M24 L= 1000/2000/3000

Other dimensions on request.

Technical information:

Fully threaded rod in acid-resistant steel grade A4-70 Quality 1.4401/AISI 316 Thread cold rolled.

Construction and mechanical characteristics in accordance with DIN 976 and ISO 898-1:2013 and NS-EN 3506-1. Color code red.

Dimensions:	Tension area mm ² , A _s	Yield, Rp0.2 N/mm ² Min.	Tensile, Rm N/mm ² f _u	Extension % A ₅	Weight Kg/m
M4x0,7	8,78	450	700	12	0,072
M5x0,8	14,2	450	700	12	0,11
M6x1,0	20,1	450	700	12	0,16
M8x1,25	36,6	450	700	12	0,3
M10x1,5	58	450	700	12	0,47
M12x1,75	84,3	450	700	12	0,73
M14x2,0	115	450	700	12	0,9
M16x2,0	157	450	700	12	1,34
M18x2,5	192	450	700	12	1,5
M20x2,5	245	450	700	12	2,1
M22x2,5	303	450	700	12	2,55
M24x3,0	353	450	700	12	3,0

Sizing Guide is available on request or can be downloaded at www.pretec.no.

Accessories:

Sleeves: B1000 A4.