

Pretec Packer type PSU-PX



Injection packer for single use. Used for sealing of drill holes close "stuff", for building pits and similar. To be used together with Pretec grouting tool.

Stock program:

Dimension / Type	For drill hole	Recommended hole	Max recommended	Torque*	Rubber length	Color
	(mm)	diameter (mm)	injection pressure (bar)	(Nm)	(mm)	code
PSU-PX 45	45	44-47	50	100-120	140	Red
PSU-PX 48	48	47-50	50	100-120	140	White
PSU-PX 51	51	50-53	50	100-120	140	Pink
PSU-PX 54	54	53-56	50	100-120	140	Yellow
PSU-PX 57	57	56-59	50	100-120	140	Blue
PSU-PX 60	60	58-62	50	100-120	140	Orange
PSU-PX 63	63	61-65	50	100-120	140	Green

^{*}Should not be less than

(PSU = Packer Single Use)

Technical information:

Compressible mechanical packer. Rubber tube expands when locking washers are pressed against packer end plate. Do not expose to direct sun light or temperature above 50°C.

Safety warning:

Do not stand in front of or next to drill hole or grouting tool when injection is taking place!

Prior to removal of grouting tool, the rock needs to "sit" for a period of time. Make sure that the injection pressure is low enough before disassembling the grouting tool.

See user guide for correct use of packer and grouting tool.

Accessories:

Pretec grouting tool for low pressure.