

## Plates for selfdrilling anchor



The plate is used against the nut (R32, R38, T40, R51) during the assembly of self-drilling rods R32/15, R38/19, and R51/26.

### Stock programme:

Spherical Plate Ø43/200x200x8 Pc-Coat (R32)

Spherical Plate Ø43/200x200x8 UB (R32)

Spherical Plate Ø56/200x200x12 UB (R38/T40)

Spherical Plate Ø56/200x200x12 Pc-Coat (R38/T40)

Flat Plate Ø60/200x200x35 with bevel UB (R51)

Flat Plate Ø60/200x200x35 with bevel Pc-Coat (R51)

### Technical Information:

Technical Information	Thickness (mm)	Weight (kg)	Quality of steel
Spherical Plate Ø43/200x200x8 Pc-Coat (R32)	8	3,1	S355/Q355
Spherical Plate Ø43/200x200x8 UB (R32)	8	3,1	S355/Q355
Spherical Plate Ø56/200x200x12 UB (R38/T40)	12	3,6	S460/Q460
Spherical Plate Ø56/200x200x12 Pc-Coat (R38/T40)	12	3,6	S460/Q460
Flat Plate Ø60/200x200x35 with bevel UB (R51)	35	10,2	S355/Q355
Flat Plate Ø60/200x200x35 with bevel Pc-Coat (R51)	35	10,2	S355/Q355

### Corrosion protection /Pc-coat

Hot-dip galvanization is carried out in compliance with NS-EN-ISO 1461 and epoxy powder coating in compliance with NS-EN 13438.

With regard to coating thickness and further information, please see Document Q/PTC-T19A Specification for Pc-Coat SVV/JBV. Please also refer to the Pc-Coat Product Data Sheet and accompanying MOM documentation.