

Stainless front washer Ø140 1.4404 / 1.4462



Front washer for use on PE-foam, membrane or rockfall netting.

PE-foam: washer will put pressure on PE-foam from nut mounted on the dry side. Highest point of washer shall be flush with PE-foam. By doing this the front washer will be pressed into the PE-foam assuring a good water stop protection on the back plate mounted on opposite side of PE foam.

Membrane: It's recommended to use a «round PE-foam gasket Ø150x5» or a «round EPDM 60 Shore Ø150x2» between membrane and washer to secure membrane against mechanical damages during installation. Nut shall be tightened firmly to assure water tightness of back plate with rubber plug mounted on opposite side of membrane.

Rockfall Netting: Washers to be used for applying different kinds of net for rock support. Can be used as front and back plate for mounting of ice-nets. Washers in desired color available on request. Either for increased visibility or to blend in with surrounding landscape.

Stock programme:

Front plate M16/Ø18 Ø140 1.4404 / 1.4462
Front plate M20/Ø21 Ø140 1.4404 / 1.4462

Front plate M24/Ø26 Ø140 1.4404 / 1.4462
Front plate M33/Ø36 Ø140 1.4404

Technical information:

Material: Stainless steel 1.4404 or duplex steel 1.4462 according to NS EN 10088-1.
Weight: 0,3 kg. Thickness 2-3 mm.

Accessories

Bolt, threaded rods, angle washer and nut. back plate 140 mm.